



GRAND LIGHTING™

GL30 XHP70_L25 IP65 LED GOBO PROJECTOR

Encased in an IP65 enclosure this fully weatherised fixture is perfect for your outdoor installation and compact and quiet to use indoors.

The high quality optical system produces a crisp vivid gobo image and the flat field gives you a crystal clear projection right to the edge.

All come with your choice of fixed lens to suit your location and built in gobo rotation that can be easily turned on or off using the front facia button.

FEATURES

- High quality optical system offers sharp image quality
- Low weight and compact design
- IP65 suitable for indoor & outdoor use
- 4 Fixed lens options available
- Built in rotation
- Quiet fanless operation making it suitable for indoor use
- Available in either black or silver
- 24 month warranty
- Cool white LED as standard. Warm white available upon request

PHOTOMETRICS

Lux values indicated are not peak values, which may be brighter. We give average lux readings taken under actual tests.

	GL30 XHP70_L25				F140 VERY NARROW LENS		
Projection Diameter (m)	0.52	0.61	0.70	0.79	0.87	0.96	1.05
Luminance (lux)	2844	2090	1600	1264	1024	846	711
Projection Distance (m)	3.0	3.5	4.0	4.5	5.0	5.5	6.0

	GL30 XHP70_L25				F100 NARROW LENS		
Projection Diameter (m)	0.68	0.80	0.91	1.03	1.14	1.25	1.37
Luminance (lux)	1707	1250	960	759	614	508	427
Projection Distance (m)	3.0	3.5	4.0	4.5	5.0	5.5	6.0

	GL30 XHP70_L25				F70 MEDIUM LENS		
Projection Diameter (m)	1.00	1.17	1.34	1.51	1.67	1.84	2.01
Luminance (lux)	1013	744	570	450	365	301	253
Projection Distance (m)	3.0	3.5	4.0	4.5	5.0	5.5	6.0

	GL30 XHP70_L25				F56 WIDE LENS		
Projection Diameter (m)	1.33	1.55	1.77	2.00	2.22	2.44	2.66
Luminance (lux)	711	522	400	316	256	212	178
Projection Distance (m)	3.0	3.5	4.0	4.5	5.0	5.5	6.0

**the F56 Wide lens is more suited to breakup gobos*

ELECTRICAL SPECIFICATIONS

- External power supply IP65 Meanwell HLG-40H-15A
- Supplied with Australian standard 3 pin plug 240V AC
- Power Supply Input Voltage: 100-240V AC
- Average Power Consumption: 30 Watts

GOBOS

- Outside diameter: 53.3mm (+0/-0.3mm)
- Maximum image diameter: 25mm (for flat field crisp projection eg logos)
- Maximum thickness: up to 5.0mm

OPTICS

- Light Source: 30W LED Capsule
- Cool white 7000k as standard (warm white 3000k available on request)
- LED Lifetime: 50,000 hours*
* figure obtained under manufacture's test conditions

PHYSICAL DIMENSIONS

- Length: 170mm (excluding lens)
- Length: 250mm (including lens)
- Width: 185mm (with knob)
- Body Height: 130mm
- Height (with Base): 215mm
- Weight: 1.5kg

